


# INSTALLER FRIENDLY SERIES® - IFS Single Phase Duplex (Demand/TD)

Single phase, duplex demand dose or timed dose, float or C-Level™ sensor controlled system for pump control and system monitoring.

The IFS duplex control panel is designed to control two (alternating) 120, 208, 240 VAC single phase pumps in water and sewage installations. The panel features an easy-to-use touch pad with display on the inner door for programming and system monitoring. The alternating action equalizes pump wear. In addition to the alternating pump control, this system provides override control should either pump fail.

The panel configuration can be easily converted in the field to either a timed dose or demand dose.

The optional C-Level™ sensor is a pressure transducer that senses the liquid level in the tank and sends a signal to the IFS panel. Pump activation levels can be adjusted by using the panel touch pad. C-Level™ sensor operating range is 3-39.9 inches (7.6-101.3 cm).




## TOUCH PAD FEATURES

- A. **Level Status Indicators** illuminate when floats or set points are activated. Alarm will activate if a float operates out of sequence.
- B. **HOA (Hand-Off-Automatic) Buttons** control pump mode with indication. Hand mode defaults to Automatic when stop level or redundant off level is reached.
- C. **Pump Run Indicators** will illuminate when pumps are called to run.
- D. **Lead/Lag Selector** toggles pump operation (alternate 1-2 and 2-1).
- E. **LED Display** shows system information including: level in inches or centimeters (C-Level™ only), mode, pumps elapsed time (hh:mm), events (cycles), alarm counter, float error count, timed dose override counter (timed dose only), and ON/OFF times (timed dose only).
- F. **NEXT Push Button** toggles display.
- G. **UP and SET Push Buttons** set pump ON/OFF times (timed dose only) and activation levels (C-Level™ only).

## PANEL COMPONENTS

1. **Enclosure base** measures 10 X 10 X 6 inches (25.4 X 25.4 X 15.24 cm). NEMA 4X (ultraviolet stabilized thermoplastic with removable mounting feet for outdoor or indoor use). **Note:** Options, voltage, and amp range selected may change enclosure size and component layout.
2. **Red Alarm Beacon** provides 360° visual check of alarm condition.
3. **Exterior Alarm Test/Normal/Silence Switch** allows horn and light to be tested and horn to be silenced in an alarm condition. Alarm automatically resets once alarm condition is cleared.
4. **Alarm Horn** provides audio warning of alarm condition (83 to 85 decibel rating).
5. **Circuit Breakers** (optional) provide pump disconnect and branch circuit protection.
6. **Power Relays** control pump by switching electrical lines. Definite purpose contactors used when pump full load amps are above 15.
7. **Float Connection Terminal Block**
8. **Incoming Control/Alarm Power & Pump Terminal Block**
9. **Control Power Indicator/Fuse** indicator light illuminates if control power is present in panel. Alarm activates if control fuse is blown.
10. **Alarm Power Indicator/Fuse** indicator light illuminates if alarm power is present in panel.
11. **Ground Lug**

**NOTE:** Schematic/Wiring Diagram and Pump Specification Label are located inside the panel on enclosure cover



Model Shown IFS31W114X8AC

Reg. Cdn Pat. & TM Off

## FEATURES

- Entire control system is UL Listed to meet and/or exceed industry safety standards
- Dual safety certification for the United States and Canada
- Standard package includes:
  - Demand Dose** - three 20' SJE MilliAmpMaster™ control switches
  - Timed Dose** - two 20' SJE MilliAmpMaster™ control switches
- Complete with step-by-step installation instructions
- Three-year limited warranty




PO Box 1708, Detroit Lakes, MN 56502  
1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: sje@sjerhombus.com

[www.sjerhombus.com](http://www.sjerhombus.com)

SEE BACKSIDE FOR COMPLETE LISTING OF AVAILABLE OPTIONS.  
SEE PRICE BOOK FOR LIST PRICE.



**MODEL IFS**

- MODEL TYPE**  
 3 = DPLX TIMED DOSE (includes option 8AC standard)  
 4 = DPLX DEMAND DOSE (includes option 8AC standard)
- ALARM PACKAGE**  
 1 = alarm package (includes test/normal/silence switch, fuse, red light & horn)
- ENCLOSURE RATING**  
 W = NEMA 4X
- STARTING DEVICE**  
 1 = 120/208/240 VAC  
 9 = 120 VAC
- PUMP FULL LOAD AMPS**  
 0 = 0-7 FLA  
 1 = 7-15 FLA  
 2 = 15-20 FLA
- PUMP DISCONNECTS**  
 0 = no pump disconnect  
 4 = circuit breaker(s)  
 120 VAC (must select starting device option 9)  
 120/208/240 VAC (must select starting device option 1)
- SWITCH APPLICATIONS**  
 H = floats (Timed dose = timer enable and alarm / Demand dose = stop, start, and lag/alarm) (select 17 option)  
 X = no floats  
 timed dose  
 demand dose  
 C = C-Level™ sensor (must select 24 option)  
 (select option 3E and/or 4A & 4D for high water alarm and/or redundant off floats)  
 timed dose  
 demand dose
- Note:** Pump down applications only.

**OPTIONS** *Listed below*

- | CODE                                | DESCRIPTION   |
|-------------------------------------|---|
| <input type="checkbox"/>            | 1J Duo alarm inputs   |
| <input type="checkbox"/>            | 3A Alarm flasher  |
| <input type="checkbox"/>            | 3B Manual alarm reset   |
| <input type="checkbox"/>            | 3E High water alarm float ( <i>must select 17 option</i> )<br><i>(Available only when Switch Applications = C)</i>  |
| <input type="checkbox"/>            | 4A Redundant off ( <i>select option 4D if floats are required</i> )<br>Demand Dose<br>Timed Dose  |
| <input type="checkbox"/>            | 4D Redundant off float<br><i>(must select 4A option) (must select 17 option)</i>  |
| <input type="checkbox"/>            | 6A Auxiliary alarm contacts, form C   |
| <input checked="" type="checkbox"/> | 8AC Display board includes: ETM counter, events (cycles) counter, alarm counter, and override counter (timed dose only). ( <i>Included as standard.</i> ) |
| <input type="checkbox"/>            | 10E Lockable latch - NEMA 4X  |
| <input type="checkbox"/>            | 10F Lightning arrestor ( <i>must select pump circuit breakers, control and alarm power combined</i> )   |
| <input type="checkbox"/>            | 10K Anti-condensation heater  |
| <input type="checkbox"/>            | 11C NEMA 1 alarm panel ( <i>must select option 6A</i> )   |
| <input type="checkbox"/>            | 11D NEMA 4X alarm panel ( <i>must select option 6A</i> )  |

- | CODE                     | DESCRIPTION  |
|--------------------------|--|
| <input type="checkbox"/> | 15A Control / Alarm circuit breaker  |
| <input type="checkbox"/> | 16A 10' cord in lieu of 20' ( <i>per float</i> )                                       |
| <input type="checkbox"/> | 16B 15' cord in lieu of 20' ( <i>per float</i> )                                       |
| <input type="checkbox"/> | 16C 30' cord in lieu of 20' ( <i>per float</i> )                                       |
| <input type="checkbox"/> | 16D 40' cord in lieu of 20' ( <i>per float</i> )                                       |
| <input type="checkbox"/> | 17C Sensor Float® / internally weighted ▲ ( <i>per float</i> )                         |
| <input type="checkbox"/> | 17D Sensor Float® / externally weighted ▲ ( <i>per float</i> )                         |
| <input type="checkbox"/> | 17G MilliAmpMaster™/ pipe clamp ● ( <i>per float</i> )                                 |
| <input type="checkbox"/> | 17H MilliAmpMaster™/ externally weighted ● ( <i>per float</i> )                        |
| <input type="checkbox"/> | 17J Sensor Float® / pipe clamp ▲ ( <i>per float</i> )                                  |
| <input type="checkbox"/> | 18A Timer override float<br>(timed dose float panel only)                              |
| <input type="checkbox"/> | 19F Fourth float to separate alarm function from lag<br>(demand dose float panel only) |
| <input type="checkbox"/> | 24E C-Level™ sensor with 4' vent tube and 20' cord                                     |
| <input type="checkbox"/> | 24F C-Level™ sensor with 4' vent tube and 40' cord                                     |
| <input type="checkbox"/> | 24G C-Level™ sensor with 8' vent tube and 20' cord                                     |
| <input type="checkbox"/> | 24H C-Level™ sensor with 8' vent tube and 40' cord                                     |

● Mechanically-activated ▲ Mercury-activated

**If additional features are required, call the factory for a quote on an Engineered Custom control panel.**

**SAMPLE**

