

WORKING VOLUME: 30380L
 TOTAL VOLUME: 33500L

CONCRETE: 35 MPa WITH 5-8% AIR ENTRAINMENT
 NON-SULPHATE RESISTANT

REINFORCING: WALLS, FLOOR, AND LID
 D9.5 HIGH TENSILE STEEL MAT W/MIN 38mm COVER
 150MM O/C E/W
 OR
 10M@ 200mm O/C E/W
 10M BAR DIAGONALS AT EACH CORNER OF LID OPENINGS




WEIGHT TOP SECTION 10580 KGS
 BOTTOM SECTION 10580 KGS
 TOTAL 21160 KGS

MAXIMUM BURIAL DEPTH: 1200mm (48")

WATER TIGHTNESS: 2X ROWS CON-SEAL CS-102 MASTIC SEALANT
 BETWEEN PIECES. SEALANT APPLIED ONSITE BY BOYD BROS
 CONCRETE ACCORDING TO MANUFACTURER'S
 RECOMMENDED METHOD.

PIPE/WALL CONNECTIONS: POLYLOK IV 100mm HIGH PRESSURE SEAL CAST
 IN CONCRETE

ACCESS OPENINGS: TUF-TITE 24X6 RISER AND LID. ADDITIONAL RISERS
 AVAILABLE. OPSD AND PUMP ACCESS LIDS AVAILABLE.



BOYD BROTHERS
 5450 CLUDDY ST, OSGOODE, ONT, K0A 2W0
 tel (613) 826-2318 fax (613) 826-3679
 toll free 888-846-6664
 website www.boydbrosconcrete.ca
 e-mail info@boydbrosconcrete.ca

bb boydbros
 concrete products

PRODUCT

30000L 2-COMPARTMENT SEPTIC TANK

SERIES NO	MODEL NO	MODELS IN SERIES
12.2	30	12.2, 13.6, 18.5, 23, 27, 30, 35
SCALE	REV	DATE
1:1250	1.0	JAN 3, 2018